

R230

Biotrituratore



7-9
m³/h*

230 x 110
Ax B mm

110
Ø max.* mm



N° 2
N° 16
N° 6

VARIANT - M

N° 24
N° 9

mm
1850

~270°



OBS
On Board System

i

Benzina + Avviamento elettrico
Petrol + Electric start
Essence + Démarreur électrique
Benzinmotor + Elektroanlasser
Gasolina + Arranque eléctrico
Benzinmotor + Elektrische start
Benzin + Elektrické startování
Benzinski + Elektro start
Benzyna + Rozruch elektryczny
Бензиновым + Электроспуском

HONDA GX630
hp21

l	l/h
10	4,8



		VARIANT -M				OBS					
	R230BH21SN	R230BH21SN-M		HONDA GX630 hp21	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	7 - 9	1860/2450 x 750 x 1540/1850	1030	615 x 585	540/605



* Materiale in entrata - Dato dipendente dal tipo di materiale e dalle condizioni di lavoro. / Input material - Data depending on the kind of material and working conditions. / Matière entrante - Donnée dépendante du type de matériel et des conditions de travail. / Eingangsmaterial - Daten, die von der Art des Materials und den Arbeitsbedingungen abhängen. / Material entrante - Dato que depende del tipo de material y de las condiciones de trabajo. / Ingangsmateriaal - Deze gegevens zijn afhankelijk van het soort materiaal en de werkomstandigheden. / Vstupní materiál - Záleží na druhu materiálu a pracovních podmínkách. / Ulazni materijal - Ovisno o vrsti materijala i uvjetima rada. / Material wsadowy - W zależności od rodzaju materiału i warunków eksploatacji. / Входной материал - Это зависит от вида материала и от условий труда.



R230BH21SN

HONDA GX630 hp21

+ OBS - On Board System



GENTLE
LAWN
STEERING

